## SACKETT CONCRETE DISTRIBUTING EQUIPMENT

#### Sackett tapered chutes

12 gauge steel



Made in 8- 10- and 12-foot lengths.

# Sackett Hicarbo interlocking concrete chute No. 546



The No. 546 HIcarbo Interlocking Concrete Chute is 18 inches by 6 inches at the top and 17 inches by 5 inches at the bottom and will telescope 15 inches to 18 inches so that any number of chutes may be used together with supports under the joints. They are of 16 Gauge steel reinforced with 1-inch x 1-inch x ½-inch angles on the edges and have a 1¾-inch x 1¾-inch x ¾6-inch angle around the top end. A Chute Harness—No. 546-I can be attached to the top end of any of these chutes. It has a 4-foot chain which will go over a ready Mix Truck chute and a 2-foot chain to hold the chute in place.

8-foot length—70 pounds 10-foot length—84 pounds 12-foot length—98 pounds



No. 665 Type B. Type A is for bottom discharge.

No.	Type	Opening	Depth	
665	Α	12" x 12"	18"	
665	В	12" x 17"		
666	A	14" x 14"	21"	
666	В	14" x 18"		

#### Hopper—20"x30" top



No. 26. Weight, 60 pounds

#### Sackett flexible spouting



No. 25. Weight per section, 30 pounds.

Flexible Spouting is for placing concrete particularly for sewer, tunnel or conduit work. Made of 14-gauge steel in 3-foot lengths, 10-inch diameter tapered to 9 inches at bottom.

192

# SACKETT CONCRETE DISTRIBUTING EQUIPMENT



No. 450.

#### Sackett rocker race dump car

Capacity			Size over-all		Diameter	Track	Weight,
List No.	cu. ft.	Length	width	height	wheel	gauge	lbs.
450-B	21	66"	52"	41"	12"	24	900
450-C	27	77"	57"	45"	12"	24	1000
450-D	36	77"	57"	51"	14"	24	1200
450-E	41	79"	60"	51"	14"	24	1400

#### **Typical Sackett Cars and Buckets**

Made up to specification on order

#### Flat car



No. 440. Built with either oak or steel top



No. 326.

#### Scoop car



No. 420.



No. 455.



No. 451.





No. 320.

## Sackett contractors' tip bucket

List No.	Capacity, cu. ft.	Width over-all	Length bucket	Depth bucket	Weight
320-A	8	35"	34"	19"	175
320-D	14	41"	39"	26"	290
320-F	21	46"	48"	28"	420
320-G	27	57"	50"	30"	540
320-I	41	58"	58"	36"	900